



**U.S.**  
**MATERIAL SAFETY DATA SHEET**  
Howes Multi Purpose Lubricator & Penetrating Oil Aerosol  
Page 1 of 6

Section 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Howes Multi Purpose Lubricator & Penetrating Oil Aerosol  
Part Number(s): HMP051, HMP053, HMP056  
Company Identification: R.B. Howes & Co., Inc.  
60 Ocean State Drive  
North Kingstown, RI 02852  
Tel: 800-438-9080 or 401-294-5500  
Emergency Telephone Number: Chemtrec 1-800-424-9300 or 703-527-3887 (24 hours)

Section 2. HAZARDS IDENTIFICATION

Emergency Overview

Level 3 Aerosol - Contents under pressure. Dark amber oil-like liquid with distinctive odor. Prolonged or repeated skin contact may cause skin irritation. Ingestion harmful or fatal if not treated. Prolonged exposure to heavy concentrations of vapors may cause irritation to mucus membranes and airway. Respiratory diseases such as asthma and skin conditions such as rashes, cuts or similar skin diseases are generally aggravated by exposure. Do not handle near excessive heat, sparks, flame or strong oxidants. Incompatible with (material to avoid) strong oxidants like liquid chlorine or concentrated oxygen. This material could be a slipping hazard if spilled.

OSHA Regulatory Status

This product contains components that are considered to be hazardous under OSHA's Hazard Communication Standard (29 CFR 1900.1200).

Potential Health Effects

Eye Contact: May cause redness and mild irritation.  
Skin Contact: Prolonged contact may cause mild irritation.  
Ingestion: Can cause cramps and nausea.  
Inhalation: Prolonged exposure may irritate the respiratory tract.  
Carcinogen: OSHA: no  
IARC: no  
NTP: no



**U.S.**  
**MATERIAL SAFETY DATA SHEET**  
Howes Multi Purpose Lubricator & Penetrating Oil Aerosol  
Page 2 of 6

**Section 3. COMPOSITION/INFORMATION ON INGREDIENTS**

<u>Component</u>	<u>CAS #</u>	<u>% by Volume</u>
Petroleum Distillates	64742-52-5	1.00 – 80.0
Aliphatic Hydrocarbon	8052-41-3	1.00 – 60.0
Liquefied Petroleum Gas	68476-86-8	15.0 – 25.0

**Section 4. FIRST AID MEASURES**

Eye contact:

Flush eyes with plenty of water for several minutes. Get medical attention if irritation persists.

Skin contact:

Wash skin with plenty of soap and water for several minutes. Get medical attention if irritation persists.

Ingestion:

Do not induce vomiting. Water may be given slowly. Contact physician immediately.

Inhalation:

If irritation or headache occurs, remove to fresh air. If signs/symptoms continue, get medical attention.

Additionally:

In all cases, if symptoms persist, contact physician.

**Section 5. FIRE FIGHTING MEASURES**

Flash point:

Concentrate: 167° F / 75°C (Rapid Flash Point Closed-Cup, ASTM D3243)

Flame projection test:

Aerosol flame extension not established.

Aerosol flame flashback not established.

Autoignition temperature:

Data not available.

Upper flammable limit:

Data not available.

Lower flammable limit:

Data not available.

Extinguishing media:

Foam, CO2, water fog or spray.



**U.S.**  
**MATERIAL SAFETY DATA SHEET**  
Howes Multi Purpose Lubricator & Penetrating Oil Aerosol  
Page 3 of 6

Fire fighting equipment:

Recommend wearing self contained breathing apparatus. Avoid breathing vapors or fumes. Cool exposed containers with water spray.

Unusual fire and explosion hazard:

Level 3 Aerosol - Contents under pressure. May form combustible mixtures at or above the flash point. Empty product containers may contain product residue. Do not pressurize, cut, heat, weld or expose containers to flame or other sources of ignition.

National Fire Protection Association (NFPA) (Level 3 Aerosol)

Flammability (red): 3  
Health (blue): 1  
Reactivity (yellow): 0  
Special (white):

**Section 6. ACCIDENTAL RELEASE MEASURES**

Leaking aerosol cans should be put into suitable container until the internal pressure has dissipated. Use appropriate personal protective equipment (PPE). (see section 8) Soak up the spill with oil absorbents, sand or other non-combustible material. Place residue in suitable, covered and properly labeled container. Dispose in accordance with federal, state and local laws.

**Section 7. HANDLING AND STORAGE**

**Handling:** Do not use product near any potential source of ignition. Avoid contact with eyes and skin. Avoid breathing vapors. Wash thoroughly after handling. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product use instructions, please see the product label.

**Storage:** NFPA 30B Level 3 Aerosol - Contents under pressure. (Level 3 aerosols have a total heat of combustion greater than 13,000 Btu/lb.) Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 49°C (120°F) to prevent cans from rupturing. Do not store near potential sources of ignition.

**Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

OSHA Permissible Exposure Limits (PEL's):  
8-hour Time Weighted Averages (TWA)

Petroleum Distillates	TWA: 2000 ppm
Aliphatic Hydrocarbon	TWA: 500 ppm
Liquefied Petroleum Gas	TWA: 1000 ppm



**U.S.**  
**MATERIAL SAFETY DATA SHEET**  
Howes Multi Purpose Lubricator & Penetrating Oil Aerosol  
Page 4 of 6

Engineering Controls

Good general ventilation should be sufficient to control airborne levels.

Respiratory Protection

Respirator use is not expected to be necessary under normal conditions of use. If application creates mist, wear a NIOSH approved respirator.

Skin Protection

For brief contact, no precautions other than wearing long sleeves should be needed. Use chemical resistant gloves such as neoprene.

Eye/Face Protection

Safety glasses with side shield, anti-splash goggles or face shield.

Hygiene Recommendations

Avoid breathing mist or vapor. Avoid contact with skin and eyes. Keep an eyewash kit available. If clothing is contaminated, remove clothing and thoroughly wash the affected area. Launder contaminated clothing before reuse.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Dark amber
Odor:	Distinctive
Physical State:	Liquid concentrate packaged in pressurized aerosol spray can
Concentrate Flash:	167° F / 75°C (Rapid Flash Point Closed-Cup, ASTM D3243)
VOC:	461 (g/l)
pH:	Not determined
Vapor Pressure:	<.1mm Hg
Vapor Density:	>1 (air = 1)
Boiling Point:	327°F / 164°C
Freezing Point:	Not determined
Solubility in Water:	Insoluble
Specific Gravity:	<.9 (H2O = 1)

Section 10. STABILITY AND REACTIVITY

Chemical Stability:	Stable under normal ambient temperature (70°F / 21°C) and pressure (14.7 psi / 760 mmHg).
Conditions to Avoid:	Combustible when exposed to excessive heat, sparks, flames or strong oxidants.
Incompatible Materials:	Contact with strong oxidizers like chlorine or concentrated oxygen.



**U.S.**  
**MATERIAL SAFETY DATA SHEET**  
Howes Multi Purpose Lubricator & Penetrating Oil Aerosol  
Page 5 of 6

Hazardous Decomposition Products: Under fire conditions: Carbon oxides (CO, CO2)

Hazardous Polymerization: Hazardous polymerization will not occur.

**Section 11. TOXICOLOGICAL INFORMATION**

	<u>Oral (rat) LD50</u>	<u>Dermal (rabbit) LD50</u>	<u>Inhalation (rat) LC50</u>
Petroleum Distillates	5,000 mg/kg	3,000 mg/kg	
Aliphatic Hydrocarbon	5,000 mg/kg	3,000 mg/kg	5,500 mg/m3

**Section 12. ECOLOGICAL INFORMATION**

No ecotoxicological studies have been conducted on this product.

**Section 13. DISPOSAL CONSIDERATIONS**

Waste management should be in compliance with federal, state and local laws.

**Section 14. TRANSPORT INFORMATION**

The information in this section is for reference only and should not take the place of a shipping paper (bill of lading) specific to an order. Please note that the proper Shipping Name / Hazard Class may vary by packaging, properties and mode of transportation.

DOT surface/ ground transportation:

Proper Shipping Name: Consumer Commodity  
Hazard Class: ORM-D

IATA (air) / IMDG (ocean) transportation:

Proper Shipping Name: Aerosols, flammable  
UN Identification Number: UN1950  
Hazard Class – Primary: 2.1  
Packing Group:  
Flash Point: 167° F / 75°C  
Packaging Note: This item, as offered by R.B. Howes, is packaged for ground transportation only.



**U.S.**  
**MATERIAL SAFETY DATA SHEET**  
Howes Multi Purpose Lubricator & Penetrating Oil Aerosol  
Page 6 of 6

49 CFR §172.101 (Appendix B) List of Marine Pollutants

This product is not a marine pollutant as defined in 49 CFR §171.8.

**Section 15. REGULATORY INFORMATION**

U.S. Regulations:

Clean Air Act (CAA) 112(r) Accidental Release Prevention Substances: No products were found.

Clean Water Act (CWA) 307 Priority Pollutants: No products were found.

Clean Water Act (CWA) 311 Hazardous Substances: No products were found.

CERCLA 302 Hazardous Substances: No products were found.

Proposition 65 California Safe Drinking Water and Toxic Enforcement Act of 1986: (Known to cause cancer): No products were found.

SARA 302/304 Emergency Planning and Notification Substances: No products were found.

SARA 313 Toxic Chemical Notification: No products were found.

TSCA Inventory Status: All components are included or are exempted from listing on the US Toxic Substances Control Act Inventory.

**Section 16. OTHER INFORMATION**

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS)

Health (Blue)	1
Flammability (Red)	4
Reactivity (Yellow)	0
Personal Protection (White)	B

MSDS PREPARATION

Prepared By: VP of Logistics  
Issue Date: September 12, 2011  
Supersedes Date: August 26, 2011

The recommendations and data presented herein are based on sources considered to be reliable. Any use inconsistent with our recommendations may affect the risk characterization. However, no warranty is expressed or implied regarding the accuracy of the data or the results obtained from the use of this information or the use of the product. R.B. Howes & Co., Inc. expressly disclaims all liability for loss or damage, including consequential loss, or injury to persons (including death) arising directly or indirectly from reliance upon the information or misuse of the material.